

Product data sheet

4812-11/5 FS

EAN-No. 4000896249572



5-pieces



Application:

Diagnosis and documentation of cavities for damage assessment

- Improved level of detail thanks to two cameras (90° and 180°) with HD resolution

5-piece set in plastic case:

- Basic unit 4812-11G
- HD probe 4812-11FS
Ø 4.9 mm, semi-flexible
- SD card 32 GB
- Micro HDMI cable (A to D) 1.8 m
- USB-C cable (A to C) 1 m
- USB-C cable (A to C) 1 m
- 90 mm (3.5 inch) large reduced-reflection LCD screen (320 x 240 pixels)
- Luminous source: 5 dimmable (10-stage) LED for optimum lighting
- Light intensity: front LED 200 – 300 Lux, side LED 550 – 700 Lux (measured at 5 cm distance)
- Optional recording in different time loops (5 · 10 · 15 · 20 minutes)
- Zoom: 1.5 x and 2 x
- Mirroring of the camera image
- Negative display of the camera image (better detection of damaged areas)
- Data transfer: USB-C
- Video output: Micro HDMI
- Operating humidity of up to 90 % (non-condensing)
- IP protection rating (basic unit): IP54
- Compatible with HAZET HD probes 4812-11FS and 4812-23AF
- Energy source: 4 x battery AA
USB interface can be used as a power source when no batteries are inserted
- Weight: 370 grams without batteries
- Dimensions (L x W x H): 276 x 123 x 54 mm
- Easy to handle
- Eyelet on the battery compartment for mounting a hand strap (drop guard)

Product data sheet

4812-11/5 FS

EAN-No. 4000896**249572**



- Thread for mounting a tripod screw connection (1/4")
 - Reset button
 - Auto power-off function, 3-way adjustable (Off · 5 · 10 minutes)
 - Record videos (MOV format) and photos (Jpeg format) with optional timestamp
 - Resolution 1920 x1080 pixels
 - 29 different menu languages can be selected
 - Use as a card reader / camera via USB connection to PC
 - Plastic box
 - Operating temperature range: 10°C – 50°C
- Current software on this item can be found at hazet.de → Software & spare parts → Downloads
- Number of tools: 5

Order Number

4812-11/5 FS



4812-11FS