Product data sheet
5108-3 CT CAL

EAN-No. 4000896**243129**

With DAkkS calibration certificate · Length: 234 mm · 2,5 – 25 Nm · 3 % · 6.3 ¼"



- User-friendly reversible ratchet
- Torque wrench **with DAkkS calibration certificate**

– SYSTEM 5000-3 CT –

- **Accuracy ± 3% of the scale value** (in direction of actuation for right-hand tightening) (5107-3 CT ± 4% accuracy of the scale value)
- For left-hand tightening, use our torque wrenches with plug connection
- Safe:
  – Haptic (close-gap release)
  – Audible (“click” sound)
- Designed for rough workshop use
- Wide range of applications for controlled screw tightening in tyre service, bicycle, passenger car and commercial vehicle applications as well as various applications in trade and industry
- Optimised sealing ring to protect against debris
- Ratchet repair set for customer-oriented self-assembly enables decades of use
- Handle with better grip for easier power transmission
- Adjustment aid with detent points for optimised operator guidance ensures safe and fast adjustment of the desired torque value by turning the handle
- Safe locking of the setting values by latching function on the rotary assembly
- Rotary assembly in triangular form prevents tool from rolling away uncontrollably
- Lock symbols indicate the respective locking status
- Can be attached to the cable loop through openings on the locking rotary assembly
- Easy-to-read, high-contrast scale
- Permanent readability due to laser marking on the scale bush
- Integrated shift lever
  5121-3CT – 5123-3CT: shift lever with idle function – reduces risk of injury and malfunction
- With calibration certificate and serial number
- Delivery in sturdy Hexa plastic box
- DIN EN ISO 6789-2:2017-07, DIN 3120, ISO 1174-1
- Made in Germany
- Output: 6.3 ¼"
- Dimensions: 234 mm
- For manual operation
- Torque range min-max: 2.5 – 25 Nm
- Accuracy: 3 %
- Scale Graduation (Nm): 0.25 Nm
- Actuating force min.-max. kg: 1.4 – 15.3 kg

HAZET-WERK – Hermann Zerver GmbH & Co. KG · 10 04 61 · 42804 Remscheid
Güldenwerther Bahnhofstrasse 25 – 29 · 42857 Remscheid · GERMANY

Product data sheet
5108-3 CT CAL EAN-No. 4000896**243129**

- Number of teeth: 20 (Opening angle 18°)
- Head Thickness a: 10.2 mm
- Head Width b: 24 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

DAkkS calibration certificate for the professional user, especially for:

- Aviation industry
- Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiabilityTorque tools in industry

Order Number	5108-3 CT CAL