Product data sheet
4812-26 G EAN-No. 4000896**281329**



Application:
Diagnosis of cavities during damage assessment

- Touchscreen colour display with Li-ION rechargeable battery and magnetic holder
- Compact design
- Easy to handle
- Swivelling magnetic base: 180° adjustable
- Thread to hold a tripod screw connection ($^{1}/_{4}$″) in the magnetic base
- Reset button
- 127 mm (5″) touch display, readable in sunlight
- Display resolution: 800 x 480 pixels
- 10-level brightness setting (5 + 5 boost)
- Zoom: 3 x
- Battery capacity display
- Recording in 3 time loops
- Auto Power Off in 4 adjustable times
- Record videos (MOV format) and photos (JPEG format)
- Image format: JPG · 1920 x 1080 pixels with optional watermark and timestamp
- Video format: MP4 · 1920 x 1080 pixels with optional watermark, timestamp and audio
- Addition of own logos as watermark possible (160 x 160 pixels)
- 64 GB SD memory card included in delivery
- SD memory useable up to 128 GB.
- Mirroring of the camera image
- Negative display of the camera image
- Designation of photos on the touchscreen
- Creating folders on the touchscreen
- Data transfer: USB-C
- HDMI port for video output
- Video output: Micro HDMI
- Battery: Li-ION rechargeable battery
- Charging time: 3.5 h

HAZET-WERK – Hermann Zerver GmbH & Co. KG · 10 04 61 · 42804 Remscheid
Güldenwerther Bahnhofstrasse 25 – 29 · 42857 Remscheid · GERMANY

Product data sheet
4812-26 G EAN-No. 4000896**281329**

- Operating time when fully charged: 4 h
- Charging device: USB charging adapter DC-5 Volts / 3 Ampere
- Operating temperature: 10 °C to 50 °C
  Temperature range: -10 °C to ~ 50°C
- Charging temperature: 0° C to 40° C
- Operating humidity of up to 90 % (non-condensing)
- IP protection rating (basic unit): IP54
- Built-in microphone
- 28 menu languages can be selected
- Use of the system as a card reader / camera via USB connection to PC
  PC software download
- Compatible with HAZET HP probes 4812-26AW, 4812-23AF and 4812-11FS
- Weight: 705 grams
- Dimensions: 161.9 x 127.9 x 46 mm

Order Number	4812-26 G