

Product data sheet

6004 CT-12

EAN-No. 4000896260041



Length: 196 mm · 0,1 – 1,2 Nm · 6 % · 



- “Ratchet function” with free-running mechanism
 - Switchable right · left · fixed
 - Allows you to work quickly
 - Trouble-free regripping when making screw connections
 - Ideal for tight installation spaces
- Excellent readability of the torque setting thanks to large, clear numerical display
- Short 36° release distance with ergonomic release behaviour and clearly audible signal
- Accuracy $\pm 6\%$ of scale value (in direction of actuation for right-hand tightening)
- Exceeding the set torque in the “right” direction of rotation is prevented by an overload clutch (“slipper”)
- Screwdriver triggers audibly and noticeably when the set value is reached and is immediately ready for operation again
- “Left” direction of actuation allows loosening without torque limitation
- Release mechanism made of high-alloy tool steel with excellent wear resistance
- Easily recognisable locking status by means of lock symbols
- Economic and sustainable thanks to calibration and repair capability at the HAZET Service Centre in Remscheid
- 1/4" inside hexagon bit holder (D 6.3 / F 6.3) with convenient engagement and ejection function
- 2K system made of high-grade, fibre-glass reinforced plastic and soft TPE grip zones
- HAZET 2-component handle · ergonomic
- Tested in accordance with DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 
- Dimensions: 196 mm
- For manual operation
- Torque range min-max: 0.1 – 1.2 Nm
- Accuracy: 6 %
- Scale Graduation (Nm): 0.01 Nm

Torque tools in industry Exemplary application of torque values 6004CT 6005CT

Order Number	6004 CT-12
Handle	HAZET 2-component handle · ergonomic