Product data sheet
6290-1 CT EAN-No. 4000896**026043**

Length: 306 mm · Torque range min-max: 5 – 60 Nm · Accuracy: 2 % · 9 x 12



- Plug connection for holding insert tools
- **Accuracy ± 2 % of the scale value** (in the direction of actuation)
  Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
  – Haptic (close-gap release)
  – Audible (“click” sound)
- With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Secure storage in safe box with inspection window
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 9 x 12
- Dimensions: 306 mm
- Net weight: 0.46 kg
- For manual operation
- Torque range min-max: 5 – 60 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 0.5 Nm
- Effective torque wrench length min.-max. l1 mm: 281.52 – 265.02 Nm
- Actuating force min.-max. kg: 1.8 – 23.1 kg
- Inside micrometre of the adjusting tool l2: 30 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Order Number	6290-1 CT

HAZET-WERK – Hermann Zerver GmbH & Co. KG · 10 04 61 · 42804 Remscheid
Güldenwerther Bahnhofstrasse 25 – 29 · 42857 Remscheid · GERMANY