

Product data sheet

6128-1 CT

EAN-No. 4000896076116



Length: 660 mm · Torque range min-max: 67,8 – 339 Nm · lbf min-max: 50 – 250 lbf.ft · Accuracy: 3 % · $\frac{1}{2}$ "



- According to US standards
- Scale graduation in lbf.ft
- **Accuracy $\pm 3\%$ of the scale value** (in direction of actuation for right-hand tightening)
For left-hand tightening, use our torque wrenches with insert tool
- Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- Safe and fast adjustment of the desired torque value by turning the handle
- **HiPer fine-tooth reversible ratchet** in 6127-1CT (90 teeth · 4° operating angle)
- Knob for additionally locking the set value
- Secure storage in safe box with inspection window
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: $\frac{1}{2}$ "
- Dimensions: 660 mm
- Net weight: 1.65 kg
- For manual operation
- Torque range min-max: 67.8 – 339 Nm
- lbf min-max: 50 – 250 lbf.ft
- Accuracy: 3 %
- Scale Graduation (lbf.ft): 2 lbf.ft
- Effective torque wrench length min.-max. l1 mm: 565.98 – 551.88 Nm
- Actuating force min.-max. kg: 12.2 – 62.6 kg
- Number of teeth: 90 (Opening angle 4°)
- Head Thickness a: 19.6 mm
- Head Width b: 44 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Order Number

6128-1 CT