Product data sheet
6292-1 CT CAL

EAN-No. 4000896**193271**

With DAkkS calibration certificate · Length: 511 mm · Torque range min-max: 40 – 200 Nm · Accuracy: 2 % · 14 x 18

- Torque wrench **with DAkkS calibration certificate**
- Plug connection for holding insert tools
- **Accuracy ± 2 % of the scale value** (in the direction of actuation)
  Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
  – Haptic (close-gap release)
  – Audible (“click” sound)
- With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Secure storage in safe box with inspection window
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 14 x 18
- Dimensions: 511 mm
- For manual operation
- Torque range min-max: 40 – 200 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 1 Nm
- Effective torque wrench length min.-max. l1 mm: 478.00 – 455.44 Nm
- Actuating force min.-max. kg: 8.5 – 44.8 kg
- Inside micrometre of the adjusting tool l2: 38.5 mm
- Head Thickness a: 23 mm
- Head Width b: 30 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

DAkkS calibration certificate for the professional user, especially for:

- Aviation industry
- Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability

Order Number	6292-1 CT CAL