

Product data sheet

9000-060

EAN-No. 4000896195312



- For all air connection nipples
- Inside thread 12.91 mm / $\frac{1}{4}$ "
- Safe separation of the connection (unwanted separation is excluded)
- No risk of injury from hose impact
- Safety coupling depressurises the connection before decoupling
- For air connection nipples:
 - Germany (standard) · Austria · Slovenia · Hungary · China · India · Portugal · Poland · Romania · Turkey NW7.2 type Rectus corresponds to HAZET air connection nipple 9000-010/3
 - Belgium · France · Netherlands · Switzerland · NW5.5 (type Aro / Orion / Milton A-Style) corresponds to HAZET air connection nipple 9000-011/3
 - Arab countries · Italy · Spain HAZET air connection nipple 9000-012/3
 - Norway · Israel / USA corresponds to HAZET air connection nipple 9000-013/3
 - Lincoln (US Automotive Lubrication System) inside thread 16.41 mm / $\frac{3}{8}$ "
- Working range: 0 – 20 bar
- One-hand operation
- Little effort during coupling and decoupling
- Omission of loud popping during coupling process
- Easy operation, even with gloves
- Brass, nickel-plated
- Air connection outlet: coupler bushing for type 1, 2, 3, 4
- Surface: nickel-plated
- Made in EU ##
- Net weight: 0.12 kg
- Operating temperature range: -15°C – 80°C

Order Number

9000-060