

Product data sheet

9530-1/4 EAN-No. 4000896**265213**



4-pieces · 65 Nm



- **4-piece set:**
 - 1 cordless drill
 - 1 quick charger
 - 2 Li-ION rechargeable batteries 18 V · 2.5 Ah (Ampere hours)
- Compact, powerful drill with extremely short head length
- Quick-action drill chuck · metal design · auto-lock function
- Drill diameter: 1.5 – 13 mm
- Electronic emergency brake
- Forward/reverse with switch-on lock
- Ergonomic non-slip, rubberised grip
- LED light with persistence afterglow
- Belt clip and drill bit storage
- Number of torque levels: 18 + 1
- Tightening torque maximum
 - Hard: 65 Nm
 - Soft: 35 Nm
- Idle speed
 - Speed 1: 0 – 500 revolutions per minute
 - Speed 2: 0 – 1800 revolutions per minute
- LED battery capacity display on battery pack
- Compatible with all 18 V battery packs in the 9500 system
- Weight (without battery): 1.14 kg
- Brushless DC motor (BLDC):
 - Longer service life, less wear, no need to change the carbon brushes
 - High efficiency and hence lower battery consumption – more compact motor enables smaller installation dimensions
- Electronic Management System (EMS) protects the machine, extends service life and increases efficiency
- Max. storage temperature: 50° C
- Metal design with thrust ring
- Sound power level: 89 db(A) Lp W
- Vibration acceleration: 1.02 m/s²

Product data sheet

9530-1/4 EAN-No. 4000896**265213**



- Dimensions: 149 mm x 69 mm x 208 mm
- Operating temperature range: -10°C – 40°C
- For impact operation
- Tightening torque maximum [Nm]: 65 Nm
- Loosening torque maximum [Nm]: 65 Nm
- Sound pressure level: 78 dB(A) Lp A

Do you know – Li-Ion batteries:

- Do not have any memory effect
- Consist of cells with 3.6 V each
- After full charge they have a higher voltage than 3.6 V i.e. 5 cells each 3.6 V = 18 V – **but** after full charge a peak voltage of up to 20 V is possible
Attention: For a longer lifetime of the battery please store it charged up to 50 to 80 % only
- Have an energy density which is twice as high as nickel cadmium batteries, for example
- Have a nominal voltage three times higher than a nickel metal hydride battery
- Require multiple complete charging cycles to reach full capacity
- Number of tools: 4

Order Number

9530-1/4



9500-025



9530-10