Product data sheet
9033 M-11 EAN-No. 4000896227129

Length: 126 mm



Application:
For processing surfaces including hard-to-reach work areas, e.g. for rust removal, paint stripping, removal of adhesive and sealant residues, as well as for cleaning/treatment of surfaces, weld seams, etc. using various abrasive media

- Heavy-duty multi-bearing gearbox with a 2.5-times longer service life compared to conventional gearboxes
- Optimised for spot repairs
- Roloc® quick-change system:
  Combine with many abrasive media
  Fast, tool-free, easy change of abrasive substances
- Grinding disc ∅ 50 mm
- Grinding disc thread: ¼″ – 20 UNF
- Exhaust air is guided through the handle
- Air connection inlet: inside thread (IG) 12.91 mm (1/4″)
- Coupler plug: Nominal size 7.2 (included)
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 95.2 db(A) Lp W
- Vibration acceleration: 1.80 m/s2
- Power in watts: 224 Watt
- Cold insulated handle
- Dimensions: 126 mm
- Net weight: 0.44 kg
- Sound pressure level: 84.2 dB(A) Lp A
- Revolutions per minute: 18000
- Air requirement: 84 l/min (1.4 l/sec)

"Mini" pneumatic tools range

- Innovative 5-slat concept for even more power than conventional drives
- High reliability and continuous operation

Order Number	9033 M-11
Handle	Cold insulated handle