

Product data sheet

9012 ECO

EAN-No. 4000896273188



Loosening torque maximum [Nm]: 1700 Nm · $\frac{1}{2}$ · Powerful twin hammer mechanism



- Loosening torque maximum [Nm]: 1700 Nm
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- Higher power output, more efficient air flow and improved air motor response torque
- Specially heat-treated internal parts for wear reduction
- One-hand operation by changeover on rear of device
- Powerful twin hammer mechanism
- Air connection inlet: inside thread (IG) 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 850 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 102.33 db(A) Lp W
- Vibration acceleration: 6.11 m/s²
- Loosening torque (maximum) determined with screw size M: 16
- Forward and reverse: four-stage (counterclockwise rotation), single-stage (clockwise rotation)
- Cold insulated handle
- Output: $\frac{1}{2}$
- Net weight: 2.15 kg
- For impact operation
- Tightening torque maximum [Nm]: 1150 Nm
- Loosening torque maximum [Nm]: 1700 Nm
- Sound pressure level: 91.33 dB(A) Lp A
- Revolutions per minute: 8491
- Air requirement: 198 l/min (3.3 l/sec)

Product data sheet

9012 ECO

EAN-No. 4000896273188



Order Number	9012 ECO
Handle	Cold insulated handle