Product data sheet
6281-2 CT EAN-No. 4000896**183326**

Length: 125.4 mm · Torque range min-max: 5 – 13 Nm · Accuracy: 4 % · 9 x 12



Application:
Regulation of the control valve at the gas tank of **VW** Up! and Caddy model years 2012 → (adjustment is necessary after installation or removal)

- Extra short construction for areas with restricted access
- Plug connection for holding insert tools
- **Accuracy ± 4 % of the scale value** (in the direction of actuation)
  Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
  – Haptic (close-gap release)
  – Audible (“click” sound)
- With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Surface: hard chrome plated
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 9 x 12
- Dimensions: 125.4 mm
- Net weight: 0.23 kg
- For manual operation
- Torque range min-max: 5 – 13 Nm
- Accuracy: 4 %
- Scale Graduation (Nm): 0.2 Nm
- Effective torque wrench length min.-max. l1 mm: 116.50 – 112.50 Nm
- Actuating force min.-max. kg: 4.4 – 11.8 kg
- Inside micrometre of the adjusting tool l2: 17.5 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Order Number	6281-2 CT

HAZET-WERK – Hermann Zerver GmbH & Co. KG · 10 04 61 · 42804 Remscheid
Güldenwerther Bahnhofstrasse 25 – 29 · 42857 Remscheid · GERMANY