Product data sheet
6005 CT-60 EAN-No. 4000896260065

Length: 198 mm · 1 – 6 Nm · 6 % · 6.3 ¼"



- Silent ratchet function, switchable to the right / left / fixed
- Makes it possible to work quickly and regrip smoothly when making screw connections
- Suitable for tight installation spaces
- Excellent readability of the torque setting thanks to large, clear numerical display
- Short 36° release distance with ergonomic release behaviour and clearly audible signal
- Accuracy ± 6 % of scale value (in direction of actuation for right-hand tightening)
- Exceeding the set torque in the “right” direction of rotation is prevented by an overload clutch (“slipper”)
- Screwdriver triggers audibly and noticeably when the set value is reached and is immediately ready for operation again
- “Left” direction of actuation allows loosening without torque limitation
- Release mechanism made of high-alloy tool steel with excellent wear resistance
- Easily recognisable locking status by means of lock symbols
- Economic and sustainable thanks to calibration and repair capability at the HAZET Service Centre in Remscheid
- 1/4″ inside hexagon bit holder (D 6.3 / F 6.3) with convenient engagement and ejection function
- 2K system made of high-grade, fibre-glass reinforced plastic and soft TPE grip zones
- HAZET 2-component T-handle · ergonomic
- Tested in accordance with DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 6.3 ¼"
- Dimensions: 198 mm
- For manual operation
- Torque range min-max: 1 – 6 Nm
- Accuracy: 6 %
- Scale Graduation (Nm): 0.1 Nm

Torque tools in industryExemplary application of torque values 6004CT 6005CT

Order Number	6005 CT-60
Handle	HAZET 2-component T-handle · ergonomic

HAZET-WERK – Hermann Zerver GmbH & Co. KG · 10 04 61 · 42804 Remscheid
Güldenwerther Bahnhofstrasse 25 – 29 · 42857 Remscheid · GERMANY