Product data sheet
9012 TT

EAN-No. 4000896**226924**

Loosening torque maximum [Nm]: 2200 Nm · 12.5 ½ · Powerful twin hammer mechanism

Application:
Long service life and high efficiency in industrial and automotive applications

- Loosening torque maximum [Nm]: 2200 Nm
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- Short design – only 128 mm
- HAZET Twin Turbo technology – high torques with compact design
- 8-blade air motor with 25% higher impact performance ensures maximum torque
- One-hand operation for right- and left-handed users
- Powerful twin hammer mechanism
- Air connection inlet: inside thread (IG) 12.91 mm (1/4″)
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 948 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 110.7 db(A) Lp W
- Vibration acceleration: 8.69 m/s2
- Loosening torque (maximum) determined with screw size M: 16
- Forward and reverse: two-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: 12.5 ½
- Net weight: 1.6 kg
- For impact operation
- Tightening torque maximum [Nm]: 1356 Nm
- Loosening torque maximum [Nm]: 2200 Nm
- Sound pressure level: 99.7 dB(A) Lp A
- Revolutions per minute: 8300

HAZET-WERK – Hermann Zerver GmbH & Co. KG · 10 04 61 · 42804 Remscheid
Güldenwerther Bahnhofstrasse 25 – 29 · 42857 Remscheid · GERMANY

Product data sheet
9012 TT EAN-No. 4000896**226924**

- Air requirement: 147.2 l/min (2.5 l/sec)

Order Number	9012 TT
Handle	Cold insulated handle