Product data sheet
9013 MTT EAN-No. 4000896258062

Loosening torque maximum [Nm]: 1890 Nm · 20 ¾″ · Powerful twin hammer mechanism



Application:
Operation of tight-fitting screw connections in narrow installation spaces with low workload in daily operation

- Loosening torque maximum [Nm]: 1890 Nm
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- Low weight
- Long service life and high efficiency in industrial and automotive applications
- **20 mm (¾″) Impact wrench in 12.5 mm (½″) housing size**
- HAZET Twin Turbo technology – high torques with compact design
- 8-blade air motor with 25% higher impact performance ensures maximum torque
- Easy to use
- Powerful twin hammer mechanism
- Air connection inlet: inside thread (IG) 12.91 mm (1/4″)
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 900 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 110.3 db(A) Lp W
- Vibration acceleration: 11.39 m/s2
- Loosening torque (maximum) determined with screw size M: 26
- Forward and reverse: three-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: 20 ¾″
- Net weight: 1.7 kg
- For impact operation
- Tightening torque maximum [Nm]: 1300 Nm
- Loosening torque maximum [Nm]: 1890 Nm

HAZET-WERK – Hermann Zerver GmbH & Co. KG · 10 04 61 · 42804 Remscheid
Güldenwerther Bahnhofstrasse 25 – 29 · 42857 Remscheid · GERMANY

Product data sheet
9013 MTT EAN-No. 4000896**258062**

- Sound pressure level: 99.3 dB(A) Lp A
- Revolutions per minute: 8000
- Air requirement: 150 l/min (2.5 l/sec)

Order Number	9013 MTT
Handle	Cold insulated handle