

Product data sheet

6294-1 CT CAL

EAN-No. 4000896193103



With DAkkS calibration certificate · Length: 718 mm · Torque range min-max: 100 – 400 Nm · Accuracy: 2 % · ± 10



- Torque wrench **with DAkkS calibration certificate**
 - Plug connection for holding insert tools
 - **Accuracy ± 2 % of the scale value** (in the direction of actuation)
Can be used for right-hand and left-hand threads by turning the insert tool
 - Safe:
 - Haptic (close-gap release)
 - Audible (“click” sound)
 - With calibration certificate and serial number
 - Safe and fast adjustment of the desired torque value by turning the handle
 - Secure storage in safe box with inspection window
 - **2-component handle** for improved feel
 - Simplified locking for adjusting the torque value
 - Viewing window for visual checking of the locking
 - Knob for additionally locking the set value
 - 4 coloured coding rings (red, yellow, green, black) for markings in the case of personalisation or special workflows
 - DIN EN ISO 6789-2:2017
 - Made in Germany
 - Output: ± 10
 - Dimensions: 718 mm
 - For manual operation
 - Torque range min-max: 100 – 400 Nm
 - Accuracy: 2 %
 - Scale Graduation (Nm): 2.5 Nm
 - Effective torque wrench length min.-max. l1 mm: 693.20 – 681.20 Nm
 - Actuating force min.-max. kg: 14.7 – 59.9 kg
 - Inside micrometre of the adjusting tool l2: 44 mm
 - Head Width b: 35.5 mm
 - **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required
- DAkkS calibration certificate** for the professional user, especially for:
- Aviation industry
 - Automobile industry
 - New-energy, wind turbines, offshore wind farms
 - Petrochemical industry (oil/gas)
- Documented traceability guarantees complete verifiability

Product data sheet

6294-1 CT CAL

EAN-No. 4000896193103



Order Number

6294-1 CT CAL