



Pipe wrench torque wrench

721/30Q 18" HD



Product no. **50184102**
GTIN **4018754360901**
Model **721/30Q 18" HD**



Label.

Pipe wrench torque wrench 721/30Q 18" HD L. 730mm

Properties.

- with permanently installed 18" STILLSON pipe wrench
- clicking type with dual stop signal
- no reset to '0' required
- the measuring element is only loaded during the tightening process
- Quick adjustment via easy-to-operate clamping lever in the handle
- Adjustment element with thumb recess prevents slipping for quick torque adjustment
- 5 selectable torque values: 180; 220; 270; 300; 350 N·m
- clicking mechanism insensitive to further and counter loads (max. up to the measuring range limit of the torque wrench)
- calibration with the perfectControl® calibration systems No. 7791, No. 7794 or the calibration system No. 7706
- simple adjustment from the external side via 2 adjustment screws without dismantling
- for controlled right-hand tightening
- with 2-component handle
- calibration certificate according to DIN EN ISO 6789-2:2017
- **accuracy $\pm 4\%$**

Benefits.

Robust torque wrench with permanently integrated STILLSON pipe wrench for precise work, e.g. on pipe screw connections, reinforcing bars, hydraulic connections or bolted joints on reinforcing bars.

5 selectable torque values, depending on the diameter, for safe, controlled tightening without over-tightening.

When the cycle is triggered, a strong tactile and audible 'click' (dual stop signal) is heard.

Lightning-fast and precise adjustment of the torque.

Precise machining of the thread and adjusting nut of the pliers enables exact positioning and reduces unwanted adjustment.

Product highlights.



PRODUCT IMAGE
IN PROGRESS

Gripping precision.

The combination of a torque wrench and the permanently integrated STILLSON pipe wrench combines powerful grip with controlled torque tightening. For efficient work, e.g. in building construction, plumbing or machine and plant engineering.



PRODUCT IMAGE
IN PROGRESS

Flexibly prepared for any task.

Thanks to the 7 selectable torque values, you can work in a controlled manner and protect the material. The lightning-fast adjustment saves time, minimises errors and ensures consistent quality - particularly valuable when requirements change frequently, on the road or in production.



PRODUCT IMAGE
IN PROGRESS

Strong grip.

With their robust STILLSON mechanism, the pliers grip reliably - whether on pipe fittings, fittings, sleeves, or even on rusted or smooth surfaces. Adjustment is conveniently stepless. A hardened adjusting screw in combination with a spring centring prevents unwanted adjustment and thus ensures maximum precision and reliability.



PRODUCT IMAGE
IN PROGRESS

Reliable handling.

The haptic feedback and a clearly audible 'click' as a dual stop signal of the mechanical cycle reliably indicate that the target value has been reached on our pipe wrench torque wrenches.



Rapid adjustment.

Easy and quick adjustment of the torque is carried out by an easy-to-operate clamping lever in the handle. The scale can be moved quickly and safely with an ergonomically shaped, non-slip adjustment element with thumb recess.



Adjustment does not require disassembly.

Quick adjustment from outside, no disassembly of the torque wrench required, with 2 adjustment points for the maximum & minimum values.

Technologies and features.




2-component handle

Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol.



Low-wear bending beam system

Our torque wrench is equipped with a low-wear release system with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not subjected to any load until the tool is in operation, which means that resetting to '0' is not necessary after use.



QuickSelect

Lightning-fast target value setting: Unlock the adjustment knob, set the value, and lock the knob again.

Technical attributes.

Anzeigeabweichung	± 4 %
Measuring range N·m	180; 220; 270; 300; 350 N·m
Length mm (L)	730 mm
Width mm (b)	90 mm
Height mm (h)	90 mm

Logistics data.

Product no.	50184102
GTIN	4018754360901
Weight (g)	4100 g
Volume (packaged, dm ³)	4.07 dm ³
Packing standard	1
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82041100
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Depth mm (IFS)	730

Width mm (IFS)	90
Height mm (IFS)	90
Weight (gross, kg)	4,450
Weight PAP (kg)	0,350
Weight PVC (kg)	0,000
Length (packaged, mm)	740
Width (packaged, mm)	110
Height (packaging, mm)	50

GTIN.



Images.





STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal