



Internal puller set, 12-pieces

11400/11401/12 L-BOXX®

Product no. **96070112**
GTIN **4018754362424**
Model **11400/11401/12 L-BOXX®**



Label.

Internal puller set 11400/11401/12 L-BOXX® Spread range 12-70mm

Properties.

- for pulling out internal bearings, bearing outer rings and bushings
- in mobile tool storage solution for industry, tradesmen, automotive and workshops
- protects tools from damage and splash water
- compatible with the entire L-BOXX® programme
- safely integrated in the modular Tool Control System (TCS)

1 tool box 136 L-BOXX®

Contains 12-pieces:

8 internal extractors **No. 11400**: Ø 12-70 mm

2 counter stays **No. 11401**: M10; M14 x 1.5

2 combination spanners **No. OPEN BOX 13**: 27; 32 mm

Benefits.

Mobile 12-piece tool set for removing internal bearings, bearing outer rings, outer housings and bushings.

The robust combination spanners (size 27/32) support direct operation of the counter stay for efficient assembly and disassembly work.

The tools are securely integrated in durable, chemical-resistant TCS inlays with precise recesses and coloured signal areas.

Suitable for pulling medium to large components with an internal diameter of 12-70 mm.


The durable ABS tool box can be seamlessly combined with other cases from the L-BOXX® programme.

Technologies and features.



Tool Control System

The intelligent modular inlay system protects and organises the tools in tool boxes, tool trolleys and workbenches. Two-colour foam inlays make checking the completeness of the tools quick and easy.



Double-T profile

Our ring, open-ended and combination spanners have an additional recess in the middle of the tool. Similar to the principle of a double-T beam, this provides a tremendous load capacity and maximum strength whilst reducing weight.




Offset Shaft Design

Our spanners are specially designed with additional reinforcement in the load zones where the greatest amount of force is transmitted - namely where the jaw meets the shank - in order to prevent deformation.



Anti-Slip-Drive

The special AS-Drive profile makes high force transmission to the flats of bolts and nuts possible without damaging them. This also prevents stripping of the screw head.



Thin-walled rings

The thin-walled diameter of our rings makes it easier to work in confined spaces. The ring wall is deeper than standard nuts, which prevents jamming.

Technical attributes.

Length mm (L)

360 mm

Logistics data.

Product no.

96070112

Length mm (internal)	311 mm	GTIN	4018754362424
Width mm (inner)	377 mm	Volume (packaged, dm ³)	24.893 dm ³
Width mm (b)	444 mm	Packing standard	1
Height mm (h)	152 mm	WEEE/ElektroG	nicht ear-pflichtig
Height mm (internal)	104 mm	Customs tariff no.	82060000
Filling volume	12,2 l	Country of origin AWR	GERMANY
Spreading range (e) min./max.	12-70 mm	Region of origin	Nordrhein-Westfalen
Ball bearing ISO	6001; 6201; 6202; 6203; 6204; 6205; 6206; 6207; 6208; 6209; 6210; 6211; 6212; 6213; 6214	Depth mm (IFS)	440
Number of tools	12 pcs.	Width mm (IFS)	365
		Height mm (IFS)	155
		Weight (gross, kg)	10,660
		Weight PAP (kg)	0,370
		Weight PVC (kg)	0,000
		Length (packaged, mm)	440
		Width (packaged, mm)	365
		Height (packaging, mm)	155

Parts list.



40082727
Combination spanner



40083232
Combination spanner



71040002
Internal puller



71040003
Internal puller



71040004
Internal puller



71040005
Internal puller



71040006
Internal puller



71040007
Internal puller



71040008
Internal puller



71040009
Internal puller



71040101
Counter stay



71040102
Counter stay



81620136
Tool box L-BOXX®



81620137
Tool card

GTIN.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal