STAHLWILLE®



Torque wrench service set MANOSKOP®

730QUICK/735/4

Product no.	**91388078**
GTIN	**4018754323296**
Model	**730QUICK/735/4**

DIN EN ISO 6789-2

Label.

Torque wrench service set MANOSKOP® Model 730QUICK/735/4 4 pcs.

Properties.

Contents 4 parts:
2 torque wrenches 730QUICK series, 8-40 N-m, 40-200 N-m
2 fine-tooth ratchets, 3/8" + 1/2", 60 teeth, working angle 6°

Top feature of the torque wrench:

- click-type
- the measuring element is only under load while force is being applied, no need for manual reset to zero
- mount for interchangeable insert/shell tools
- QuickRelease safety lock
- rapid setting thanks to easy-action locking lever in the handle
- ergonomically designed, non-slip adjuster with a thumb recess
- optimised convex handle for strain-free working
- dual stop signal
- can be applied for either clockwise or anticlockwise tightening by turning the inserts over
- any force applied to the tool after the 'click' or applied in the opposite direction to the current function – e.g. forcible loosening of a jammed screw - does not act on the trigger mechanism and cannot cause damage to it
- calibration using perfectControl® calibrating unit No 7794 or calibration system No 7706. Readjustment does not require disassembly.
- With certificate
- display deviation value ± 4%

Product highlights.



Robust tool box.
The robust tool box is particularly resilient thanks to its durable ABS plastic. It has a high-quality, chemical-resistant hard foam insert to hold the tools securely in place. The fasteners are particularly easy to use and can be ordered individually as spare parts.



Everything at a glance.
The laser-engraved contents in the lid insert provide an optimal overview of the tools within.



Rapid adjustment.
Easy and quick adjustment of the torque is carried out by an easy-to-operate clamping lever in the handle. The scale can be moved quickly and safely with an ergonomically shaped, non-slip adjustment element with thumb recess.



Adjustment does not require disassembly.
Quick adjustment from outside, no disassembly of the torque wrench required, with 2 adjustment points for the maximum & minimum values.

Technologies and features.



Low-wear bending beam system
Our torque wrench is equipped with a low-wear release system with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not subjected to any load until the tool is in operation, which means that resetting to '0' is not necessary after use.



QuickRelease
The QuickRelease safety lock prevents unintentional loss of sockets and insert tools. These click securely into place, and are only released again at the push of a button for a quick tool change. In transducers: The QuickRelease safety lock helps you to quickly mount and change transducers. The transducers lock into the calibration system and only unlock again at the push of the buttons.



DIN EN ISO 6789-2
Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.

Technical attributes.

Measuring range N·m	8-40|40-200 N·m
Measuring range ft-lb	-|30-145 ft·lb
Scale division N·m	1|5 N·m
Scale division ft-lb	-|5 ft·lb
Length mm (L)	480 mm
Width mm (b)	285 mm
Height mm (h)	85 mm
Number of tools	4 pcs.

Logistics data.

Product no.	91388078
GTIN	4018754323296
Weight (g)	3588 g
Volume (packaged, dm3)	11.628 dm3
Packing standard	1
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82041100
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Depth mm (IFS)	480
Width mm (IFS)	285
Height mm (IFS)	85
Weight (gross, kg)	3,588
Weight PAP (kg)	0,219
Weight PVC (kg)	0,000
Length (packaged, mm)	480
Width (packaged, mm)	285
Height (packaging, mm)	85

Parts list.



50184004
MANOSKOP® torque wrench



50184020
MANOSKOP® torque wrench

GTIN.

4 018754 323296

STAHLWILLE Eduard Wille GmbH
Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0
info@stahlwille.de · www.stahlwille.com
© STAHLWILLE Eduard Wille GmbH, Wuppertal