



Tension wire cutter 40°

2025



Product no. **56020255**
GTIN **4022668015444**
Model **20255 40° 630**

Label. Steel reinforcing wire cutter 40° 48HRC L.630mm

Properties.

- Infinitely adjustable
- Limit stop with extra large buffer zone
- For commercially available reinforcing steel III + IV to DIN 488 - strength approx. 550 N / mm² - as well as for prestressing steel and tempered steel wire up to a strength of 1570 N / mm² (HRC 48)
- With 40° offset blades, for cutting protruding prestressing wires on concrete walls

Benefits.

Real craftsmanship leaves nothing to chance – the perfect symbiosis of professional skills and excellent tools unleashes exciting results. ALARM has been committed to this principle since 1867

Technical attributes.

Length mm (L)	630 mm
Physical length [mm]	650 mm
DIN	DIN 488
Hardness	48 HRC
Cutting performance 19 HRC	9 mm
Cutting performance 40 HRC	8 mm
Cutting performance 48 HRC	7 mm

Logistics data.

Product no.	56020255
GTIN	4022668015444
Weight (g)	2806 g
Volume (packaged, dm ³)	5.814536 dm ³
Packing standard	1
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82034000
Country of origin AWR	GERMANY
Region of origin	Thüringen
Depth mm (IFS)	650

Width mm (IFS)	180
Height mm (IFS)	47
Weight (gross, kg)	2,806
Weight PAP (kg)	0,000
Weight PVC (kg)	0,000
Length (packaged, mm)	652
Width (packaged, mm)	182
Height (packaging, mm)	49

GTIN.



Spare part(s), spare part(s) for.



56020273
Cutterhead with
retaining screws



56020402
Lower part for bolt-
cutters

Images.





STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Tel.: +49 202 4791-0

info@alarm-werkzeug.de · www.alarm-werkzeuge.de

© STAHLWILLE Eduard Wille GmbH, Wuppertal