Click-Torque C 3 set 2 for cement screwdriving, 40-200 Nm, 11 pieces



EAN:	4013288217561	**Size:**	545x132x95 mm
Part number:	05075681001	**Weight:**	3366 g
Article number:	Click-Torque C 3 Set 2	**Country of origin:**	TW
		Customs tariff number:	82041100

- For fitting security-relevant cement screws with defined torque moments as per screw manufacturer instructions
- Click-Torque C 3 torque wrench with reversible ratchet (measuring range: 40-200 Nm; precision ± 3 % as per DIN EN ISO 6789-1:2017-07)
- 8790 C Impaktor socket wrench inserts for the application with compressed air or electrically driven impact wrenches with 12.5 mm = 1/2" drive (13 mm to 21 mm)
- Extension 8894 SC, short, ½" with cross-bore and the ring socket to secure the locking ring/locking pin of machine operated tools
- 11-piece set in premium textile tool box


11-piece set for fitting security-relevant cement screws with defined torque moments as per screw manufacturer instructions. With Take it easy tool finder with colour coding and size stamping - for easy and fast location of the required tool.

Web link
https://www.wera.de/en/05075681001

Wera - Click-Torque C 3 Set 2
05075681001 - 4013288217561

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

For fitting cement screws



The tool set is particularly suitable for fitting security-relevant cement screws with defined torque moments as per screw manufacturer instructions.

For electric or pneumatic wrenches



The Impaktor technology ensures above-average service life of the Impaktor socket wrench plug-ins even under extreme conditions.

Cross hole and ring socket



Thanks to the hole and the ring socket, the tools can be held securely on the power tool with a safety pin or an O-ring.

Click-Torque Wrench series



Click torque wrench in unmistakable Wera design.

Exact



Precision of ±3 % as per DIN EN ISO 6789-1:2017-07.

Easy and safe



Easy setting and saving of the desired torque value; easy to read on main and fine scales.

Setting with Speed



With audible and tactile locking when the scale values are reached.

Release mechanism



On reaching the desired torque value, an audible and tactile mechanism is triggered.

Web link
https://www.wera.de/en/05075681001

Wera - Click-Torque C 3 Set 2
05075681001 - 4013288217561

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Set contents:

Click-Torque C 3 torque wrench with reversible ratchet, 40-200 Nm, 1/2" x 40-200 Nm



05075622001	1x	1/2" x 40-200 Nm

8790 C Impaktor socket with 1/2" drive, 13 x 38 mm



05004570001	1x	13 x 38 mm
05004571001	1x	14 x 38 mm
05004572001	1x	15 x 38 mm
05004573001	1x	16 x 38 mm
05004574001	1x	17 x 38 mm
05004575001	1x	18 x 38 mm
05004576001	1x	19 x 38 mm
05004577001	1x	20 x 38 mm
05004578001	1x	21 x 38 mm

8894 SC extension, short, 1/2", 1/2" x 125 mm



	1x	1/2" x 125 mm

Web link
https://www.wera.de/en/05075681001

Wera - Click-Torque C 3 Set 2
05075681001 - 4013288217561

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de